

THROW 'n GO BERM

- No assembly required
- Walls lay flat when not in use
- Fastest deployment in the industry for portable spill containment systems (simply throw and go)
- Can be driven on at any angle
- 2' wall availability permits smaller footprint
- In the event of a spill, walls automatically rise to create a catch basin
- Optional built-in track mats help prevent damage to the berm
- Berm contains no working parts which would malfunction
- Meets EPA regulations for spill containment
- Heavy-duty 30 ounce fabric is appropriate for water, hydrocarbons, and most chemicals
- Easily emptied through 3/4" drains
- Patent No US 2010/0294779 A1
- Available in Desert Tan; OD Green; and Black
- Custom sizes available



Part #	Dimensions	Gallons
TG5512	5' x 5' x 12"	187 gal
TG8812	8' x 8' x 12"	479 gal
TG101012	10' x 10' x 12"	748 gal
TG123612	12' x 36' x 12"	3563 gal
TG145412	14' x 54' x 12"	6119 gal

This data is provided for informational purposes only. GeoCHEM, Inc. makes no warranties as to the suitability or the fitness for a specific use or merchantability of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check GeoCHEM, Inc. for current updates.

SPEC SHEET – Throw n’Go Berm

Gallons and dims by wall size

Width	Length	6"/ Gallons	6"/Outside Dims	12"/ Gallons	12"/Outside Dims
10'	10'	375	12'-1" X 12'-1"	750	13'-6" X 13'-6"
10'	20'	716	12'-1" X 22'-1"	1528	13'-6" X 23'-6"
12'	36'	1580	14'-1" X 38'-1"	3320	15'-6" X 39'-6"
14'	54'	2786	16'-1" X 56'-1"	5805	17'-6" X 57'-6"
Width	Length	18"/ Gallons	18"/Outside Dims	24"/Gallons	24"/Outside Dims
10'	10'	1125	14'-10" X 14'-10"	1500	16'-4" X 16'-4"
10'	20'	2436	14'-10" X 24'-10"	3441	16'-4" X 43'-4"
12'	36'	5220	16'-10" X 40'-10"	7280	18'-4" X 42'-4"
14'	54'	9055	18'-10" X 58'-10"	12537	20'-4" X 60'-4"

Fabric: 30 oz. Hydrocarbon / chemical resistant

Standard Colors: Black, Tan, Green

Base Fabric Type	US	Metric
	Polyester	
Base Fabric Weight (nominal)	8 oz/yd ²	270 g/m ²
Thickness	36 mils min	0.91 mm
Weight	30.0+ ₋₂ oz/yd ²	1020+ ₋₇₀ g/m ²
Tear Strength, Tongue D751B	120/120 lb min	534/534 N min
Breaking Yield Strength ASTM D 751, Grab Tensile, Procedure	625/600 lb min	2780/2670 N min
Low Temperature ASTM D 2136,	Pass @ -40 F	Pass @ -40 C
Dimensional Stability ASTM D 1204, 212 F- 1 hr	2.5% max each direction	
Adhesion - Heat Sealed Seam ASTM D 751, Dielectric Weld	25 lb/2 in min	111 N/5 cm min
Bursting Strength ASTM D 751, Ball Tip	1000 lb min	4450 N
Hydrostatic Resistance ASTM D 751, Method A	800 psi min	540 N/sq cm min
Blocking Resistance ASTM D 751, 180 F/82 C	# 2 Rating max	
UV Resistance	8000 hrs	
Puncture Resistance ASTM D 4833	220 lb min	1110 N min

This data is provided for informational purposes only. GeoCHEM, Inc. makes no warranties as to the suitability or the fitness for a specific use or merchantability of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check GeoCHEM, Inc. for current updates.