





# TECHNICAL DATA SHEET / ; 9C: @C

## ; EC: @C FOR REPAIR

### PRODUCT DATA

**Physical Test Requirements.** Elastomeric asphalt will conform to the following physical test requirements per NYS DOT Standard Specification 701-11:

**New York State DOT Contact: Guy Hildreth 518-485-5431**

TESTS	Alligator Glue*
Resilience	Pass
5 hr. Compressive Strength	2,100+ psi
24 hr. Compressive Strength	3,800+ psi
7-Day Tensile	500+ psi
7-Day Tear	200+ lbf/in
Pot Life	10 minute

- Quick Set - Less Than 10 Min
- Minimal Prep - No Primer Required
- Shorter Traffic Closures - Reduced Labor Costs
- Waterproofs Both Asphalt and Concrete
- Protection Against Oils, Gasoline Hydraulic/Brake Fluids and Water
- Longer Lasting Than Conventional Repair Materials
- Odorless and Vaporless

\*The information shown in the table are the results of the New York State DOT Materials Testing Laboratory test of Alligator Glue, which is the black polymer-only version of GeoSet.

### STORAGE & RETURN

Store in cool, dry area, in closed containers and out of direct sunlight in rooms with ambient temperatures maintained between 32° and 80° F.

Our products are manufactured to conform to the specifications published in our product data sheets. We do not warranty the performance of @C materials or equipment. Please see our website for more details: <http://www.geocheminc.com/disclaimer.htm>

#### DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

### HEALTH AND SAFETY INFORMATION

**EYE CONTACT:** Immediately flush eyes with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and treated by medical personnel.

**INHALATION:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is labored, give oxygen. Consult medical personnel.

**SKIN CONTACT:** Wash material off the skin with plenty of soap and water. If redness, itching, or a burning sensation develops, get medical attention. Wash contaminated clothing and decontaminate footwear before reuse.

**INGESTION:** Do not induce vomiting. Give 1 or 2 glasses of water to drink and refer person to medical personnel. Never give anything by mouth to an unconscious person.

Sales & Procurement Center - Phone No. (907) 562-5755 ~ Fax No. 206.219.3740  
WA State Sales - Phone No. (206) 774.8777 ~ Toll Free: 1 (800) 490.5320