



## **SG 1300**

STRATAGRID is geogrid reinforcement for soil. These high performance geogrids are constructed of high molecular weight and high tenacity polyester yarns utilizing a complex knitting process and polymer coating to provide superior engineering properties. Yarns are precision knitted into a dimensionally stable, uniform network of apertures providing significant tensile reinforcement capacity. STRATAGRID is engineered to be mechanically and chemically durable, in both the harsh construction installation phase and in aggressive soil environments (pH range from 3-9).

Property	Test Method	English	Metric
Ultimate Strength	ASTM D-6637 Method A	20,556 lbs/ft	300 kN/m
Tensile Modulus @ 2% Strain	ASTM D-6637 Method A	2,055 lbs/ft	30 kN/m
Tensile Modulus @ 5% Strain	ASTM D-6637 Method A	5,139 lbs/ft	75 kN/m
Tensile Strength @ 10% Strain	ASTM D-6637 Method A	14,389 lbs/ft	210 kN/m
Creep Reduction Factor		1.55	1.55
Creep Limited Strength		13,262 lbs/ft	193.5 kN/m
LTDS (SM, SC, CL, ML)	LTDS or Tal	10,960 lbs/ft	160 kN/m
LTDS (SW, SP, SM, SC)	LTDS or Tal	10,960 lbs/ft	160 kN/m
LTDS (GP, GW, GM, GC, SW, SP, SM, SC)	LTDS or Tal	10,484 lbs/ft	153 kN/m
LTDS (GP)	LTDS or Tal	9,645 lbs/ft	140.8 kN/m
LTDS (GP)(2)	LTDS or Tal	7,535 lbs/ft	110 kN/m
Molecular Weight (min.)	GRI GG8	25,000 g/mol	25,000 g/mol
Carboxyl End Group Count (max.)	GRI GG7	30 Meg/kg	30 Meg/kg

Reduction Factor	Value
RF(id) Soil - 25mm minus, D50 ≤ 0.2mm (SM, SC, CL, ML)	1.10
RF(id) Soil - 25mm minus, D50 ≤ 5mm (SW, SP, SM, SC)	1.10
RF(id) Soil - 25mm minus, D50 ≤ 10mm (GP, GW, GM, GC, SW, SP, SM, SC)	1.15
RF(id) Soil - 50mm minus, D50 ≤ 0.20mm (GP)	1.25
RF(id) Soil - 50mm minus, D50 $\leq$ 0.30mm (GP)	
$RF(d) (3 \le pH \le 9) (PET - CEG < 30, MW > 25,000)$	1.10

Soil Interaction Coefficient	Value
Silts/Clay (ML, CL)	0.6 - 0.7
Sandy Silts & Clay (SC,GC)	0.7 - 0.8
Poorly-Graded Sand & Gravel, Silty Sand (GP, GM, SP, SM)	
Well-Graded Gravel, Sand Gravel Mix, Well-Graded Sand (SW, GW)	

Roll Size	Roll Diameter	Area	Weight
12.5' x 200'	16 in	278 sys	450 lbs

This information is provided for reference only and is not intended as a warranty or guarantee. GeoCHEM, Inc. assumes no liability in connection with the use of this information (1/2017).

GeoCHEM,Inc. - Phone: (907) 562.5755 ~ Fax: 206.219.3740 WA State Sales - Phone: (206) 774.8777 ~ Toll Free: 1(800)490.5320

http://www.geocheminc.com